



## FVG PE woven material clear, PE-covered

**Special material for use as fruit cover/rain caps, door/  
gable and side ventilation as well as protection film.**



Product Description	100% PE woven material, 2-side covered UV-stabilized approx. 48 months (400kly)							
Colour	transparent							
Weight	100 + 50 + 50 gr / sqm							
Shading effect	20%							
Light transmission	80%							
Temperature resistance	-40° / +80°C							
Tensile strength	1000N / 5cm							
Tear resistance	210N							
Tolerance	+/- 5%							
Widths (m)	1,50	2,00	2,50	3,00	4,00	4,50	5,50	8,00
	*larger dimension ready made possible*							
Length (m)	As required							

FVG warrants that this product conforms to its specifications. The test results are being provided based on current production. Products warranty is based on FVG Warranty terms for greenhouse film and installation /handling guidelines. Buyer is responsible to verify the suitability of the product for his particular use. The amount of any claim against FVG and FVG's liability relative to the product's properties or performance, shall in no event exceed the purchase value of the product. In no event shall FVG be liable for loss of profit or special, indirect or consequential damages. Since the mechanism of action of the anti-dripping and anti-fogging effect as well as the reduction of insects and petal blackening are complicated and depend on many parameters that are out of control (climatic conditions, greenhouse type, crop, pollination method etc.), no warranty is given regarding the duration or effectiveness of these functions and we do not undertake liability for any damage relevant to those functions. More information at [www.fvg-folien.de](http://www.fvg-folien.de)