



FVG FLOOR, Woven Ground Cover Material

Product Description	UV-stabilized, 550 kly = 5 years in Middle Europe							
Colour	Black with green squares every 15cm							
Weight	100 gr / sqm							
Tensile strength	EN ISO 10319				kN/m 20/14 (warp / weft)			
Punct.resistance	EN ISO 10319				%13/12 (warp / weft)			
Water permeability	Ca. 10 l / sqm / sec							
Pipe pushing force	2350 N							
Widths (m)	0,52	0,75	1,05	1,31	1,57	1,65	2,10	2,62
	3,30	4,20	5,25	bigger dimensions ready made				
Lengths (m)	100							

Product Description	UV-stabilized, 550 kly = 5 years in Middle Europe	
Colour	White with green stripes	
Weight	100 gr / sqm	
Tensile strength	EN ISO 10319	20/147 kN/m (warp / weft)
Punct. resistance	EN ISO 10319	%13/12 (warp / weft)
Water permeability	Ca. 10 l / sqm / sec	
Pipe pushing force	2350 N	
Widths (m)	3,30	4,20
	bigger dimensions ready made	
Lengths (m)	100	

FVG warrants that this product conforms to its specifications. The test results are being provided based on current production. Products warranty is based on FVG Warranty terms for greenhouse film and installation /handling guidelines. Buyer is responsible to verify the suitability of the product for his particular use. The amount of any claim against FVG and FVG's liability relative to the product's properties or performance, shall in no event exceed the purchase value of the product. In no event shall FVG be liable for loss of profit or special, indirect or consequential damages. Since the mechanism of action of the anti-dripping and anti-fogging effect as well as the reduction of insects and petal blackening are complicated and depend on many parameters that are out of control (climatic conditions, greenhouse type, crop, pollination method etc.), no warranty is given regarding the duration or effectiveness of these functions and we do not undertake liability for any damage relevant to those functions. More information at www.fvg-folien.de