



Greenhouse Tunnel film FVG Euro ®

The uv-b allrounder



Product Description	Tunnel film, uv stable 48 months in central Europe climatic conditions, seasonal use even longer							
Colour	transparent							
Thickness	180 µ (tolerance +/- 5%, spot +/- 20%)							
Tensile strength	EN ISO 527-3				MD 22 N/mm ²		TD 22 N/mm ²	
Elongation at break	EN ISO 527-3				MD 500%		TD 600%	
Dart drop	ISO 7765-1				Fold: >550		Flat:>550	
Total transmission	EN 2155-5				approx. 88-89% (400-700nm)			
Share of diff. light	EN 2155-9				approx. 23% (400-700nm)			
Widths (m)	6,50	8,50	9,00	9,50	10,00	12,00	12,50	13,00
	14,00	14,50	15,00	15,50	16,00			
Length (m)	As required							

FVG warrants that this product conforms to its specifications. The test results are being provided based on current production. Products warranty is based on FVG Warranty terms for greenhouse film and installation /handling guidelines. Buyer is responsible to verify the suitability of the product for his particular use. The amount of any claim against FVG and FVG's liability relative to the product's properties or performance, shall in no event exceed the purchase value of the product. In no event shall FVG be liable for loss of profit or special, indirect or consequential damages. Since the mechanism of action of the anti-dripping and anti-fogging effect as well as the reduction of insects and petal blackening are complicated and depend on many parameters that are out of control (climatic conditions, greenhouse type, crop, pollination method etc.), no warranty is given regarding the duration or effectiveness of these functions and we do not undertake liability for any damage relevant to those functions. More information at www.fvg-folien.de